



Tubo in gomma termoplastica multistrato con spirale in acciaio zincato incorporata e rinforzo in fibra poliestere, per aspirazione e passaggio liquidi aggressivi.

Multi-layer thermoplastic rubber hose with embedded galvanised steel spiral with polyester yarn reinforcement, for suction and delivery of aggressive liquids.



SUPERFICI LISCE
SMOOTH SURFACE



FLESSIBILITÀ
FLEXIBILITY



RESISTENZA ALL'ABRASIONE
ABRASION RESISTANCE

ISO 4649: <150 mm³



TEMPERATURA D'IMPIEGO
TEMPERATURE RANGE

-25° C + 80° C



RESISTENZA CHIMICA
CHEMICAL RESISTANCE

tabella TPV



RESISTENZA ALLO SCHIACCIAMENTO
CRUSHING RESISTANCE

Tubo in gomma termoplastica

Inner hose made of thermoplastic rubber

Spirale in acciaio

Steel spiral

Tubo in gomma termoplastica

Cover made of thermoplastic rubber

Rinforzo in fibra poliestere

Polyester yarn reinforcement

Ø INTERNO Ø I.D.	Ø INTERNO Ø I.D.	Ø ESTERNO Ø O.D.	PESO WEIGHT	RAGGIO CURVATURA BENDING RADIUS	PRESS. ESERCIZIO WORKING PRESS.	PRESS. SCOPPIO BURSTING PRESS.	SOTTOVUOTO VACUUM	LUNG. ROTOLI COIL LENGTH
inc	mm	mm	g/m	mm	20° 60° bar	bar	m H ₂ O	mt
3/4	19	28	380	70	15 8	45	9	60
1	25	35,5	580	80	14 6	42	9	60
	30	40,5	650	85	10 6	30	9	60
1 1/4	32	42,5	700	90	10 6	30	9	60
	35	47	850	95	10 6	30	9	60
1 1/2	38	50	920	100	10 6	30	9	30
	40	52	970	110	10 6	30	9	30
1 3/4	45	57	1100	120	10 6	30	9	30
2	50	63	1280	130	10 5	30	9	30
	60	73	1550	160	9 4	27	9	30
2 1/2	63	76	1600	180	9 4	27	9	30
3	76	91	2350	230	8 4	24	9	30
	80	95,5	2400	250	8 4	24	9	30
3 1/2	90	105,5	2750	280	8 4	24	9	30
4	102	118,5	3100	310	7 3	21	9	30

