

# OIL & PETROLEUM DISPENSING/FUELING

## FLEXSTEEL® HARDWALL



### APPLICATION:

FLEXSTEEL® HARDWALL hose is for dispensing pump applications that require a hardwall construction for full flow and no internal spring guards. It provides excellent kink resistance, low computer creep and long service life.

### CONSTRUCTION:

#### Tube:

Black Nitrile synthetic rubber (ORS)

#### Reinforcement:

Wire braid

#### Cover:

Black, Green, Red, Blue or Yellow oil, ozone and abrasion resistant Chemivic® (Buna-N-Vinyl) synthetic rubber (ORS)

### TEMPERATURE:

-40°C/+60°C (-40°F/+140°F)

### BRANDING:

»Goodyear 559N, Made in USA. ID" (IDmm) UL, CUL. LISTED FLEXSTEEL HARDWALL GASOLINE HOSE«

### STANDARDS:

ISO 1307  
UL 330 and CUL Approved

ID		OD	WP		BR	W	SL
mm	inch	mm	bar	psi	mm	g/m	m
15,9	5/8	25,4	16	232	80	570	RCL*
19,1	3/4	28,7	16	232	100	650	RCL*
25,4	1	35,1	16	232	150	850	RCL*

\* Reels or Coupled Lengths  
Hose safety factor (burst pressure) 4:1.

Air & Water

Air Heavy  
Duty

Water

Multi-  
purpose

Oil &  
Petroleum  
Transfer  
Dock  
Dispensing/Fueling

Chemical

Food

Cleaning  
&  
Washdown

Marine

Material  
Handling

Steam

Welding

Appendix  
Additional  
Products  
Chemical Charts  
General Information



Information is valid throughout 2008. Due to continual product improvements, Veyance Technologies, Europe reserves the right to alter specifications without prior notice. For the most current product information please contact your local Veyance Technologies, Europe. Sales/Marketing office.