



Tubo in mescola poliuretano antiabrasivo e gomma termoplastica con rinforzo in fibra poliestere a corredo delle macchine che richiedono la normativa ATEX, per utensileria pneumatica in genere, aerografi, pistole per verniciatura.

Antiabrasive polyurethane and thermo-plastic rubber compound hose with polyester yarn reinforcement supplied with machines required by the ATEX regulation, for pneumatic tools in general, airbrushes, paint sprayers.

	SUPERFICI LISCE SMOOTH SURFACE	*****
	FLESSIBILITÀ FLEXIBILITY	****
	RESISTENZA ALL'ABRASIONE ABRASION RESISTANCE	***
	TEMPERATURA D'IMPIEGO TEMPERATURE RANGE	-15° C + 60°C
	RESISTENZA CHIMICA CHEMICAL RESISTANCE	tabella PU
	RESISTENZA ALLO SCHIACCIAMENTO CRUSHING RESISTANCE	***
	CONDUTTIVO CONDUCTIVE	secondo ASTM D 257 Resistività superficiale ≤ 10 ⁴ Ohm VALORE VARIABILE NEL TEMPO According to the ASTM D 257 Surface resistance ≤ 10 ⁴ Ohm Varying value with time.

Ø INTERNO Ø I.D.	Ø INTERNO Ø I.D.	Ø ESTERNO Ø O.D.	PESO WEIGHT	RAGGIO CURVATURA BENDING RADIUS	PRESS. ESERCIZIO WORKING PRESS.	PRESS. ESERCIZIO WORKING PRESS.	PRESS. ESERCIZIO WORKING PRESS.	LUNG. ROTOLI COIL LENGTH
inc	mm	mm	g/m	mm	bar 20° C	bar 40° C	bar 60° C	mt
1/4	6	10	70	20	20	17	15	100
5/16	8	12	85	22	20	17	15	60
3/8	10	15	130	38	20	17	15	50
1/2	13	19	195	65	20	17	115	30
5/8	16	23	250	60	20	17	15	25

Tubo in PU conduttivo
PU conductive hose

Tubo MIX PVC - gomma
MIX PVC hose - Rubber

Tubo in PVC - gomma
PVC hose - Rubber

Rinforzo in fibra poliestere
Polyester yarn reinforcement

