BULK TRANSFER

BLACK SOFTWALL

APPLICATION:	For the discharge of dry bulk cement from tank truck and in-plant service.
CONSTRUCTION	
TUBE:	1/8" (static dissipating/static conductive) Black Tufsyn® synthetic rubber. Available in 1/8", 3/16", and 1/4" tube gauges.
COVER:	Black Plioflex® synthetic rubber with white spiral stripe (wrapped impression)
REINFORCEMENT:	Spiral-plied synthetic fabric
TEMPERATURE:	-25°F to 180°F (-32°C to 82°C)
PACKAGING:	100' lengths, coiled and polywrapped
BRANDING:	Continuous spiral brand "Goodyear™ Black Softwall."
COUPLINGS:	Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Goodyear's Insta-Lock Cam & Groove Fittings with this product. See page 254 for available Insta-Lock products.
NON-STOCK/SIZES:	400' minimum order
ORDER CODES:	549-152 (1/8" tube gauge) 549-149 (3/16" tube gauge) 549-148 (1/4" tube gauge)

NOM. ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
4	101.6	4.42	112.27	50	0.34	1.38	2.05
5	127.0	5.44	138.18	50	0.34	1.82	2.71
6	152.4	6.45	163.83	50	0.34	2.25	3.35