



### Applications

Pressure service line for benzene, toluene, and xylene based paints, lacquer, varnish, and certain chemicals.

Also for industrial paint spray equipment.

### Advantages

- Hose cover resistant both to abrasion and to corrosive chemicals.
- Free from silicone.
- Antistatic tube.

### Technical description

**Inner tube:** solvent paints resistant NBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** oil and weather resistant NBR/PVC, green, smooth.

**Temperature range:** -20 °C to +100 °C.

**Electrical properties:** antistatic tube,  $R < 10^6 \Omega/m$ .

### Couplings/Fittings

Special paint hose couplings are recommended.

ID		Wall thickness	OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Price
mm		mm	mm		bar	bar	mm	kg/m	m	€/m
6.0	± 0.4	3.3	12.6	± 0.5	20	60	60	0.14	40 - 80 - 120	6.89 €
8.0	± 0.5	3.5	15.0	± 0.6	20	60	70	0.17	40 - 80 - 120	7.02 €
10.0	± 0.5	3.75	17.5	± 0.6	20	60	90	0.24	20 - 40 - 80 - 120	7.92 €
13.0	± 0.6	4.0	21.0	± 0.7	20	60	110	0.28	40 - 80 - 120	9.42 €
16.0	± 0.7	4.5	25.0	± 0.8	20	60	130	0.38	40 - 80 - 120	12.57 €

**Length in blue = stock item.** Length in black = non stock (consult us for minimum quantity of order).

Branding:



TRELLEBORG

MULTIKLER - Made in France