



AIR / WATER - 20 bar

PAINTED STEEL



In accordance with directive
Atex 94/9 II 3 GD c X

FIXED



Supplied with:

- polyurethane hose
- brass fitting
- brass swivel joint
- "viton" seals



S. 288

Article

8288.100

8288.102

8288.103

8288.104

8288.105

Hose supplied

without hose

13m - 10x14,5 (972.113)

15m - 8x12 (971.115)

10m - 6x10 (971.010)

15m - 6x10 (971.015)

Connection

inlet

outlet

M3/8"G

F3/8"G

M3/8"G

M3/8"G

M3/8"G

M1/4"G

M3/8"G

M1/4"G

M3/8"G

M1/4"G

S. 328

8328.100

8328.102

8328.103

8328.104

8328.105

without hose

15m - 10x14,5 (972.115)

18m - 8x12 (971.118)

8m - 13x19 (976.108)

12m - 13x19 (976.112)

M3/8"G

F3/8"G

M3/8"G

M3/8"G

M3/8"G

M1/4"G

M1/2"G

M1/2"G

M1/2"G

M1/2"G

S. 378

8378.100

8378.102

8378.103

8378.104

8378.105

without hose

20m - 10x14,5 (972.120)

20m - 8x12 (971.120)

10m - 13x19 (976.110)

15m - 13x19 (976.114)

M3/8"G

F3/8"G

M3/8"G

M3/8"G

M3/8"G

M1/4"G

M1/2"G

M1/2"G

M1/2"G

M1/2"G

S. 438

8430.100

8438.101

8438.102

without hose

10m - 13x19 (976.111)

15m - 13x19 (976.115)

F1/2"G

F1/2"G




F1/2"G

M1/2"G

F1/2"G

M1/2"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	Kg *
S. 288	186	140	196	226	110	310	300	320	-	0,037	from 7 to 12
S. 328	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 378	186	140	196	226	110	400	390	410	20	0,068	from 10 to 17
S. 438	186	140	196	226	115	450	420	460	20	0,098	from 14 to 21

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.
The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

