




OIL AND SIMILAR PRODUCTS - 150 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.400
8330.402

SWIVELLING



Article

-

-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



Hose supplied

Connection

inlet outlet

without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.312)	F1/2"G	M1/2"G

without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.312)	F1/2"G	M1/2"G
17m - 3/8" (995.317)	F1/2"G	M1/2"G

without hose	F1/2"G	F1/2"G
10m - 1/2" (996.310)	F1/2"G	M1/2"G
15m - 1/2" (996.315)	F1/2"G	M1/2"G

for ABS hose reels Series 430 see page 152

without hose	F1/2"G	F1/2"G
20m - 1/2" (996.320)	F1/2"G	M1/2"G
25m - 1/2" (996.325)	F1/2"G	M1/2"G

without hose	F1"G	F1"G
15m - 3/4" (997.515)	F1"G	M3/4"G
20m - 3/4" (997.520)	F1"G	M3/4"G
15m - 1" (998.515)	F1"G	M1"G
without hose	F1/2"G	F1/2"G
30m - 1/2" (996.330)	F1/2"G	M1/2"G

without hose	F1"G	F1"G
30m - 1" (998.530)	F1"G	M1"G

S. 330

S. 390

S. 430

S. 530

S. 540

S. 560

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

