



WATER MAX 130°C - 100 bar

PAINTED STEEL



In accordance with directive Atex
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8330.200
8330.201

SWIVELLING



Article

-
-

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- AISI 304 stainless steel swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F1/2"G	F 3/8"-1/2"G
12m - 3/8" (995.313)	F1/2"G	M3/8"G

S. 330

S. 390

S. 430

S. 530

S. 540

S. 560

8390.200
8390.202

8430.200
8430.201
8430.202

8380.200
8380.202

8420.200
8420.201
8420.202

without hose
17m - 3/8" (995.318)

without hose
10m - 1/2" (996.311)
15m - 1/2" (996.316)

F1/2"G F3/8"-1/2"G
F1/2"G M3/8"G

F1/2"G F1/2"G
F1/2"G M1/2"G
F1/2"G M1/2"G

for ABS hose reels Series 430 see page 152

without hose
20m - 1/2" (996.321)

F1/2"G F1/2"G
F1/2"G M1/2"G

without hose
20m - 3/4" (997.320)
15m - 1" (998.315)

F1"G F1"G
F1"G M3/4"G
F1"G M1"G

without hose
30m - 1" (998.330)

F1"G F1"G
F1"G M1"G

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and therefore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

