



AIR / WATER - 20 bar

PAINTED STEEL



In accordance with directive ATEX
94/9 IIB 2 GD c T4 T135 °C X

FIXED



Article

8290.100
8290.101
8290.104

S. 290

SWIVELLING



Article

-
-
-
-
8380.100
8380.102

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- brass swivel joint
- "viton" seals



Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G
10m - 3/8" (995.210)	F3/8"G	M3/8"G
15m - 1/4" (993.215)	F3/8"G	M1/4"G
without hose	F3/8"G	F3/8"G
12m - 3/8" (995.211)	F3/8"G	M3/8"G
without hose	F3/8"G	F3/8"G
18m - 3/8" (995.217)	F3/8"G	M3/8"G
without hose	F1/2"G	F1/2"G
12m - 3/8" (995.212)	F1/2"G	M3/8"G
18m - 3/8" (995.218)	F1/2"G	M3/8"G
10m - 1/2" (996.210)	F1/2"G	M1/2"G
15m - 1/2" (996.215)	F1/2"G	M1/2"G
without hose	F1/2"G	F1/2"G
20m - 1/2" (996.220)	F1/2"G	M1/2"G
25m - 1/2" (996.225)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
15m - 3/4" (997.215)	F1"G	M3/4"G
20m - 3/4" (997.220)	F1"G	M3/4"G
15m - 1" (998.215)	F1"G	M1"G
without hose	F1/2"G	F1/2"G
30m - 1/2" (996.230)	F1/2"G	M1/2"G
without hose	F1"G	F1"G
30m - 3/4" (997.230)	F1"G	M3/4"G
40m - 3/4" (997.240)	F1"G	M3/4"G
20m - 1" (998.220)	F1"G	M1"G
30m - 1" (998.230)	F1"G	M1"G
without hose	F1/2"G	F1/2"G

for ABS hose reels Series 430 see page 152

8430.100
8430.101
8430.102
8430.103
8430.104

S. 430

8420.100
8420.101
8420.102
8420.103
8420.104

8530.100
8530.101
8530.102

S. 530

8520.100
8520.101
8520.102

8540.100
8540.101
8540.102
8540.103
8540.105
8540.106

S. 540

8550.100
8550.101
8550.102
8550.103
8550.105
8550.106

8560.100
8560.101
8560.103
8560.104
8560.105
8560.106

S. 560

-
-
-
-
-
-

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reel.

The **template** supplied facilitates drilling of the holes and there fore hose reel fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reel installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

